

Aluminum Electrolytic Capacitor Specification

Series	KLH	35 V 470 μ F	Part No.	KLH-035V471MG160-T/A5.0
Customer No.	/		Case size	Φ D 10 X L 16
Specification	Items		Standard	
	Operating temperature range		- 40 ~ + 105 $^{\circ}$ C	
	Capacitance tolerance		\pm 20% (20 $^{\circ}$ C , 120Hz)	
	Dissipation factor (MAX)		(Less than) 0.12 (20 $^{\circ}$ C , 120Hz)	
	Leakage current (MAX)		(Less than) 164.5 μ A (20 $^{\circ}$ C 35 V 2 min)	
	Impedance (MAX)		0.07 Ω (100KHZ, 20 $^{\circ}$ C)	
	Ripple current (MAX)		780 mArms (100KHz , 105 $^{\circ}$ C)	
	Load life		3000 hrs	
Outline	Sleeve color		Deep Green	
	Marking color		White	
	(Dimensions)			
	<p style="text-align: center;">Copper clad steel wire(tinned)</p> <p>The drawing shows a side view of the capacitor with a cylindrical body and a vent. Labels include 'Vent', 'Sleeve', 'Markings', and 'Copper clad steel wire(tinned)'. Dimensions are given as 10+0.5 MAX for height, 16 + 1.5 max for body length, 15min for sleeve length, and 4min for lead length. Lead diameter is Φ0.6\pm0.05. Polarity is indicated with \oplus and \ominus symbols. The end view shows a circular body with a 'Flat Rubber' seal and a 'Lead space' of 5.0\pm0.5 mm. A note specifies '[Remarks: Taping space: 5.0(+0.8-0.2)]' and '(unit): mm'.</p>			
Recorder	(The first edition) : 2016-10-31			
Wrote by: LUOLI		Checked by: DINGCHANGHUA		Approved by: SHENZHIHONG