

Aluminum Electrolytic Capacitor Specification

Series	KRM	400 V 68 μ F	Part No.	KRM-400V680MM400
Customer No.	339499		Case size	Φ D22X L40
Specification	Items		Standard	
	Operating temperature range		- 40 ~ + 105 $^{\circ}$ C	
	Capacitance tolerance		\pm 20% (20 $^{\circ}$ C , 120Hz)	
	Dissipation factor (MAX)		(Less than) 0.15(20 $^{\circ}$ C , 120Hz)	
	Leakage current (MAX)		(Less than) 816 μ A (20 $^{\circ}$ C 400 V 1 min)	
	Ripple current (MAX)		465 mArms (120Hz , 105 $^{\circ}$ C)	
	Impedance (MAX)		/	
	Load life		2000 hrs	
Outline	Sleeving pipe basic		PVC	
	(Dimensions)			
	<p>The drawing shows a side view and a top view of the capacitor. The side view labels include: 'Vent' at the top left, 'Sleeve' pointing to the outer casing, 'Copper clad steel wire(tinned)' pointing to the leads, 'Markings' on the capacitor body, and dimensions: '22+0.5 MAX' for height, '40+2.0max' for body length, '15min' for lead length, and '4min' for lead spacing. The top view shows a circular cross-section with a diameter of $\Phi 1.0 \pm 0.05$ and a 'Lead space' of 10 ± 0.5. Polarity symbols (+ and -) are shown near the leads. A note '(unit):mm' is at the bottom right.</p>			
Recorder	(The first edition) :2016-5-18			
Wrote by: Luoli		Checked by: Dingchanghua		Approved by: Shenzhihong