

Aluminum Electrolytic Capacitor Specification

Series	KRM	35 V 470 μ F	Part No.	KRM-035V471MG125-T/A5.0
Customer No.	341133		Case size	Φ D10X L 12.5
Specification	Items		Standard	
	Operating temperature range		- 55 ~ + 105 °C	
	Capacitance tolerance		\pm 20% (20°C , 120Hz)	
	Dissipation factor (MAX)		(Less than) 0.12 (20°C , 120Hz)	
	Leakage current (MAX)		(Less than) 164.5 μ A (20°C 35 V 1 min)	
	Ripple current (MAX)		410 mArms (120Hz , 105°C)	
	Impedance (MAX)		/	
	Load life		2000 hrs	
Outline	Sleeving pipe basic		PVC	
	(Dimensions)			
	<p> The drawing shows a side view of the capacitor with a sleeve. Labels include: Vent, Sleeve, Copper clad steel wire(tinned), Markings, $\Phi 0.6 \pm 0.05$, 10 ± 0.5 MAX, 12.5 ± 1.5 max, 15min, 4min, and polarity symbols \oplus and \ominus. The top view shows a circular cross-section with a lead space of 5.0 ± 0.5 mm and a diameter of $\Phi 0.6 \pm 0.05$ mm. </p> <p>[Remarks: Taping space: 5.0(+0.8-0.2)]</p> <p style="text-align: right;">(unit) :mm</p>			
Recorder	(The first edition) :2016-5-18			
Wrote by: Luoli		Checked by: Dingchanghua		Approved by: Shenzhihong