

Aluminum Electrolytic Capacitor Specification

Series	KRJ	10 V 100 μ F	Part No.	KRJ-010V101MC070-T/A5.0
Customer No.	342577		Case size	Φ D5X L 7
Specification	Items		Standard	
	Operating temperature range		- 55 ~ + 105 $^{\circ}$ C	
	Capacitance tolerance		\pm 20% (20 $^{\circ}$ C , 120Hz)	
	Dissipation factor (MAX)		(Less than) 0.19 (20 $^{\circ}$ C , 120Hz)	
	Leakage current (MAX)		(Less than) 10 μ A (20 $^{\circ}$ C 10 V 2 min)	
	Ripple current (MAX)		70 mArms (120Hz , 105 $^{\circ}$ C)	
	Impedance (MAX)		/	
	Load life		1000 hrs	
Outline	Sleeving pipe basic		PVC	
	(Dimensions)			
	<p> Sleeve Copper clad steel wire(tinned) Φ0.45\pm0.05 Markings 5+0.5 MAX 7+1.0max 15min 4min Lead space 2.0\pm0.5 [Remarks: Taping space:5.0(+0.8-0.2)] (unit) :mm </p>			
Recorder	(The first edition) :2016-5-18			
Wrote by: Luoli		Checked by: Dingchanghua		Approved by: Shenzhihong