

## Aluminum Electrolytic Capacitor Specification

Series	KRM	16 V 100 $\mu$ F	Part No.	KRM-016V101MC110-T/A2.5
Customer No.	/		Case size	$\Phi$ D 5 X L 11
Specification	Items		Standard	
	Operating temperature range		- 55 ~ + 105 $^{\circ}$ C	
	Capacitance tolerance		$\pm$ 20% ( 20 $^{\circ}$ C , 120Hz )	
	Dissipation factor (MAX)		( Less than ) 0.16 ( 20 $^{\circ}$ C , 120Hz )	
	Leakage current (MAX)		( Less than ) 16 $\mu$ A ( 20 $^{\circ}$ C 16 V 1 min )	
	Impedance (MAX)		/	
	Ripple current (MAX)		110 mArms ( 120Hz , 105 $^{\circ}$ C )	
	Load life		2000hrs	
Outline	Sleeving pipe basic		PVC	
	( Dimensions )			
	<p style="text-align: center;">Copper clad steel wire(tinned)</p> <p style="text-align: center;">Sleeve</p> <p style="text-align: center;">Markings</p> <p style="text-align: center;"><math>\Phi</math>0.5<math>\pm</math>0.05</p> <p style="text-align: center;">5+0.5 MAX</p> <p style="text-align: center;">11 +1.5max</p> <p style="text-align: center;">15min</p> <p style="text-align: center;">4min</p> <p style="text-align: center;">Flat Rubber</p> <p style="text-align: center;">Lead space 2.0<math>\pm</math>0.5</p> <p style="text-align: center;">【Remarks:Taping space: 2.5 (+0.8-0.2)】</p> <p style="text-align: center;">(unit):mm</p>			
Recorder	(The first edition) : 2017-4-24			
Wrote by: LUOLI		Checked by: DINGCHANGHUA		Approved by: SHENZHIHONG