

Aluminum Electrolytic Capacitor Specification				
Series	KRM	400 V 4.7 μ F	Part No.	KRM-400V4R7MG125-L/C4.0
Customer No.	/		Case size	Φ D 10 X L 12.5
Specification	Items		Standard	
	Operating temperature range		- 40 ~ + 105 $^{\circ}$ C	
	Capacitance tolerance		\pm 20% (20 $^{\circ}$ C , 120Hz)	
	Dissipation factor (MAX)		(Less than) 0.15 (20 $^{\circ}$ C , 120Hz)	
	Leakage current (MAX)		(Less than) 56.4 μ A (20 $^{\circ}$ C 400 V 1 min)	
	Impedance (MAX)		/	
	Ripple current (MAX)		66 mArms (120Hz , 105 $^{\circ}$ C)	
	Load life		2000hrs	
Outline	Sleeving pipe basic		PVC	
	(Dimensions)			
	<p style="text-align: center;">Copper clad steel wire(tinned)</p> <p style="text-align: center;">Sleeve</p> <p style="text-align: center;">Φ0.6\pm0.05</p> <p style="text-align: center;">Vent</p> <p style="text-align: center;">10+0.5 MAX</p> <p style="text-align: center;">Markings</p> <p style="text-align: center;">12.5 +1.5max</p> <p style="text-align: center;">4.0\pm0.5</p> <p style="text-align: center;">Flat Rubber</p> <p style="text-align: center;">Lead space 5.0\pm0.5</p> <p style="text-align: right;">(unit):mm</p>			
Recorder	(The first edition) : 2017-4-24			
Wrote by: LUOLI		Checked by: DINGCHANGHUA		Approved by: SHENZHIHONG