

Aluminum Electrolytic Capacitor Specification

Series	KRM	25 V 2200 μ F	Part No.	KRM-025V222MH200-T/A5.0
Customer No.	360873		Case size	Φ D12.5X L 20
Specification	Items		Standard	
	Operating temperature range		- 55 ~ + 105 $^{\circ}$ C	
	Capacitance tolerance		\pm 20% (20 $^{\circ}$ C , 120Hz)	
	Dissipation factor (MAX)		(Less than) 0.16 (20 $^{\circ}$ C , 120Hz)	
	Leakage current (MAX)		(Less than) 550 μ A (20 $^{\circ}$ C 25 V 1 min)	
	Ripple current (MAX)		1000 mArms (120Hz , 105 $^{\circ}$ C)	
	Impedance (MAX)		/	
	Load life		2000 hrs	
Outline	Sleeving pipe basic		PVC	
	(Dimensions)			
	<p> The drawing shows a side view of the capacitor with a sleeve. Labels include: Vent, Sleeve, Copper clad steel wire(tinned), Φ0.6\pm0.05, Markings, 12.5\pm0.5 MAX, 20\pm2.0max, 15min, and 4min. The top view shows a circular cross-section with a lead space of 5.0\pm0.5 mm. Polarity symbols \oplus and \ominus are shown. </p> <p>[Remarks: Taping space:5.0(+0.8-0.2)]</p> <p>(unit) :mm</p>			
Recorder	(The first edition) :2016-5-18			
Wrote by: Luoli		Checked by: Dingchanghua		Approved by: Shenzhihong