





Chinese Qr code



English Qr code

TB02 Series thermal protection


TB02 protector has small size、Quick action、Long Life and so on, widely used in battery pack、Lithium protection board、Medical Devices、Electric thermal appliances、Fire cable, integrated circuits over-current double protection of overheating Operating temperature 30°C-160°C.



TB02-BB8D	Plastic	15mm×5.4mm×2.4m	AC250V2A	10,000Cycles
TB02-BB1D	Iron	11.5mm×5mm×2.4m	DC24V 3A	10,000Cycles

TB05 Series thermal protection

TB02 protector has small size、Quick action、Long Life and so on, widely used in battery pack、Lithium protection board、Medical Devices、Pumps,integrated circuits over-current double protection of overheating
Operating temperature 30℃-155℃.



TB05-BB5D	Plastic	15mm×7.0mm×3.7mm	AC250V 5A DC24V 10A	10,000Cycles
TB05-BB1D	Iron	15mm×6.5mm×3.2mm		10,000Cycles
TB05-A	Plastic	18mm×8.0mm×4.0mm		6,000Cycles
TB05-B	Iron	20mm×7.5mm×3.5mm		6,000Cycles
TB05-C	Plastic	15mm×6.5mm×3.5mm		10,000Cycles
TB05-D	Iron	15mm×6.0mm×3.0mm		10,000Cycles


TB10/25/50 Series thermal protection

TB10/25/50 used in battery pack、motor over heating or current protection.

TB10-BB5D	Plastic	18mm×9.3mm×4.5mm	AC250V 10A	10,000Cycles
TB10-BB1D	Iron	18mm×7.9mm×3.5mm		10,000Cycles
TB25-BB5D	Plastic	22mm×10mm×5.0mm	AC250V 25A	10,000Cycles
TB25-BB1D	Iron	22mm×9.0mm×4.0mm		10,000Cycles
TB50-BB5D	Plastic	25mm×10.6mm×5.2mm	AC250V 50A	10,000Cycles
TB50-BB1D	Iron	25mm×12.0mm×6.2mm		10,000Cycles

17AM/7AM Series thermal protection


17AM is a miniature, snap-in thermal devices. It is widely used in cleaners, pumps, and various other applications. Operating temperature 45 °C -165 °C.



17AM (A)	23mm×10.5mm×4.8mm	AC250V 9A	10,000Cycles
17AM (B)	25mm×10.5mm×4.8mm	DC24V 9A	10,000Cycles

5AP/6AP/3MP Series thermal protection

5AP/6AP as sensitive interrupters work, which is widely used in power windows, seat adjuster motors, wipers and a variety of other applications.




5AP	18.7mm×8.0mm×2.9mm	DC15V 20A	10,000Cycles
6AP/3MP	23mm×9.3mm×3.6mm	AC250V 20A	10,000Cycles

TB11 Series thermal protection

TB11 inside can be embedded in PTC, so can reduce the rotary type equipment such as mixer for automatic reset and the risk of sudden reboot.


Operating temperature 30°C-180°C。



TB11-BB5D	18.9mm×7mm×3.7mm	AC250V 11A	10,000Cycles
TB11-BY5D	18.9mm×7mm×3.7mm	AC110~250V 11A	10,000Cycles
TB11-BY5L	18.9mm×7mm×3.7mm	DC24 11A	10,000Cycles

TB11-W series thermal protector


TB11-W series thermal protector is widely used in hair dryer.



TB11-W	31.5mm×5.4mm×3.3mm	AC250V 11A	10,000Cycles
--------	--------------------	------------	--------------

KSD series thermal protector

KSD series thermostat are widely used in water dispensers, electric water heater, sandwich toaster, dishwasher, dryer, disinfection cabinet, microwave oven, electric coffee pot, electric cooking pot, refrigerator, air conditioner gluing machine, office equipment, car seat heater with electric heating, etc. Opening temperature 0 °C to 180 °C.




N0	Part	Material	Type	N0	Part	Material	Type
1	case	aluminum	A1050 H24	7	Spring	QBe	QBe2.0
		copper	H62	8	M-c	Ag/Cu	AgNi10/Cu
2	Thermal slices	Bimetallic	BR-1/BH-2	9	Plate	copper	H62
3	Holder	plastic	PPS	10	S-c	Ag/Cu	AgNi10/Cu
		ceramic	AL ₂ O ₃	11	H-long	copper	T2
4	Ejector	ceramic	AL ₂ O ₃	12	S-long	copper	T2
5	H-short	copper	T2	13	Base	P/C	PPS/AL ₂ O ₃
6	S-short	copper	T2	14	lug	copper	H62

KSD	Φ 16.0mm×11.8mm	AC250V 16A	100,000Cycles
-----	-----------------	------------	---------------

TB06 Series thermal protection

TB06 series thermal protector is widely used in electric tools, battery overheat over-current protection .The jump system characteristics for the slow action. Operating temperature 5°C-150°C 。



TB06 (A)	27mm×9.1mm×4.6mm	DC24V 6A	10,000Cycles
TB06 (B)	24mm×9.1mm×4.6mm	DC24V 6A	10,000Cycles



Baozhu Electric Appliance Co.,Ltd

Address: Jinghe Caoba industrial zone Baozhu industrial park Yangzhou
city in Jiangsu province Baoying.

International telephone: 0086-514-88381888

Fax: 0086-514-88274888