

<b>ALUMINUM ELECTROLYTIC CAPACITORS</b>		APPROVAL NO.
		<b>6499</b>
<b>BXJ 35 VC 22 (M)</b>		SERIES
		RATING
		CASE SIZE
		BXJ
		35 V 22 $\mu$ F
		$\varnothing$ 5 x 5.3 L

**A. DIAGRAM OF DIMENSIONS**

Recommended Solder land on PC board

Case code	ØD	L	A	B	C	W	P	a	b	c
E56	5	5.3	5.3	5.3	5.9	0.5-0.8	1.4	1.4	3.0	1.6

**B. ELECTRICAL CHARACTERISTICS**

- A. OPERATING TEMPERATURE RANGE : **-55 ~ +105 °C**
- B. RATED VOLTAGE : **35 V<sub>DC</sub>**
- C. SURGE VOLTAGE : **44 V<sub>DC</sub>**
- D. CAPACITANCE TOLERANCE : **± 20%** at 20 °C, 120Hz
- E. LEAKAGE CURRENT : Lower **7.7  $\mu$ A**, after 2 minutes at 20 °C
- F. DISSIPATION FACTOR (TAN $\delta$ ) : Lower **0.12** at 20 °C, 120Hz
- G. MAX. RIPPLE CURRENT : **155 mArms** at 105 °C, 100kHz
- H. TEMPERATURE CHARACTERISTIC :  
 (Max. Impedance ratio)  $Z(-25\text{ }^\circ\text{C}) / Z(20\text{ }^\circ\text{C}) = \underline{2}$   
 $Z(-55\text{ }^\circ\text{C}) / Z(20\text{ }^\circ\text{C}) = \underline{3}$  (at 120Hz)
- I. LOAD LIFE : The following specifications shall be satisfied when the capacitors are restored to 20 °C after the rated voltage is applied for **2,000** hours at **105 °C**.
  - # Capacitance change  $\leq$  **±30 %** of the initial value
  - # Tan $\delta$   $\leq$  **300 %** of the initial specified value
  - # Leakage Current  $\leq$  The initial specified value
- J. SHELF LIFE : The following specifications shall be satisfied when the capacitors are restored to 20 °C after exposing them for **1,000** hours at **105 °C** without voltage applied. The rated voltage shall be applied to the capacitors for a minimum of 30 minutes, at least 24 hours and not more than 48 hours before the measurement.
  - # Capacitance change  $\leq$  **±30 %** of the initial value
  - # Tan $\delta$   $\leq$  **300 %** of the initial specified value
  - # Leakage Current  $\leq$  The initial specified value
- K. CLEANING CONDITIONS : Solvent - proof
- L. OTHERS : Satisfied characteristics KS C IEC 60384-4

※ IMP.(20 °C, 100kHz) : **0.80 ( $\Omega$ )** ↓

