



Size: 80*25*25mm

Model		S-24-12
Output	DC output voltage	12V
	Output voltage tolerance	±1%
	rated output current	2A
	Output current range	0~2A
	Output power	24W
	Ripple and noise	100mVp-p
	DC adjustment range	±5%
	Setup、rise、hold time	200ms,100ms,30ms/230VAC.
Input	AC input voltage range	100~240VAC 47~63Hz
	AC input current (max)	0.45A
	Efficiency	≥82%
	AC inrush current(max)	Cold start ,40A/230V
	Leakage current(max)	<3.5mA/240VAC
Protection characteristic	Overload protection	120%~150%rated output power ,start loading protection Protection mode: hiccup mode, Auto-recovery
	Over voltage protection	115%~135%Shut down O/P, Auto-recovery
	Over temp protection	≥105°CShut down O/P, Auto-recovery
Environment	Working temperature	-10 °C~+60 °C
	humidity	20%~90%RH
Safety	Withstand voltage	I/P-O/P: 1.5KVAC I/P-FG: 1.5KVAC O/P-FG :0.5KVAC
	Insulation resistance	I/P-O/P ; I/P-FG , O/P-FG : 100M Ohms/500VDC
Else	Weight/packing	0.05kg/300PCS/14kg/15kg CARTON: 48*38.5*25CM