

Aluminum Electrolytic Capacitor Specification				
Series	KLH	400 V 68 μ F	Part No.	KLH-400V680MK250
Customer No.	/		Case size	Φ D 18 X L25
Specification	Items		Standard	
	Operating temperature range		- 25 ~ + 105 $^{\circ}$ C	
	Capacitance tolerance		\pm 20% (20 $^{\circ}$ C , 120Hz)	
	Dissipation factor (MAX)		(Less than) 0.15 (20 $^{\circ}$ C , 120Hz)	
	Leakage current (MAX)		(Less than) 816 μ A (20 $^{\circ}$ C 400 V 2 min)	
	Impedance (MAX)		1.15 Ω (120HZ, 20$^{\circ}$C)	
	Ripple current (MAX)		750mA_{rms} (100kHz , 105$^{\circ}$C)	
	Load life		5000hrs	
Outline	Sleeving pipe basic		PVC	
	(Dimensions)			
	<p style="text-align: center;">Copper clad steel wire(tinned)</p> <p style="text-align: center;">Sleeve Φ0.8\pm0.05</p> <p style="text-align: center;">Vent</p> <p style="text-align: center;">18+0.5 MAX</p> <p style="text-align: center;">Markings</p> <p style="text-align: center;">25 + 2.0max 15min 4min</p> <p style="text-align: center;">Flat Rubber</p> <p style="text-align: center;">Lead space 7.5\pm0.5</p> <p style="text-align: right;">(unit):mm</p>			
Recorder	(The first edition) : 2017-4-24			
Wrote by: LUOLI		Checked by: DINGCHANGHUA		Approved by: SHENZHIHONG