


SPECIFICATION FOR APPROVAL

CUSTOMER:			DATE:				
PART NO: LCB3216-601Y-N			DWG.NO: TE9903312				
CUSTOMER PART NO:			CUST.DWG.NO:				
(1) DIMENSIONS (UNIT: mm) 			A	3.2 ± 0.2	m/m		
			B	1.6 ± 0.2	m/m		
			C	1.1 ± 0.2	m/m		
			D	0.5 ± 0.3	m/m		
			E		m/m		
			F		m/m		
			G		m/m		
			H		m/m		
			I		m/m		
			J		m/m		
(2) ELECTRICAL REQUIREMENTS							
Z (Ω)	$600 \pm 25\%$	TEST FREQ				100MHz / 100mV	
RDC (Ω)	0.06 (MAX)	TEST FREQ					
IDC (mA)	3000 (MAX)	TEST FREQ					
TEST INSTRUMENTS HP 4338A MILLIOHMMETER HP 4291B RF IMPEDANCE / MATERIAL ANALYZER			APPROVED BY				
			吳載敏				
			CHECKED BY				
			張明德				
			DRAWN BY				
			黃慧診				

CORE MASTER ENTERPRISE CO., LTD.

TEL:886-2-8919-1288 FAX:886-2-8919-1298 WEB:www.coremaster.com.tw

TEST DATA

CUSTOMER :					DATE :				
PART NO: LCB3216-601Y-N					DWG.NO: TE9903312				
CUSTOMER PART NO :					CUST.DWG.NO :				
ITEM	Z (Ω)	RDC (Ω)	IDC (mA)		DIMENSION (UNIT : mm)				
FREQ	100MHz /100mV				A	B	C	D	
SPEC	600 ± 25%	0.06 (MAX)	3000 (MAX)		3.2 ± 0.2	1.6 ± 0.2	1.1 ± 0.2	0.5 ± 0.3	
1	515.3	0.042	OK		3.25	1.60	1.08	0.50	
2	536.5	0.047	OK		3.21	1.62	1.10	0.52	
3	529.3	0.043	OK		3.23	1.60	1.08	0.50	
4	517.5	0.043	OK		3.22	1.64	1.09	0.54	
5	531.0	0.042	OK		3.25	1.62	1.12	0.53	
6	519.1	0.043	OK		3.24	1.63	1.10	0.50	
7	522.0	0.044	OK		3.22	1.61	1.08	0.51	
8	534.6	0.041	OK		3.21	1.62	1.09	0.55	
9	515.4	0.041	OK		3.22	1.64	1.10	0.52	
10	543.4	0.042	OK		3.23	1.62	1.08	0.51	
\bar{X}	526.4	0.043			3.23	1.62	1.09	0.52	
R	28.1	0.006			0.04	0.04	0.04	0.05	
						APPROVED BY			
						吳載敏			
						CHECKED BY			
						張明德			
						DRAWN BY			
						黃慧診			

CORE MASTER ENTERPRISE CO., LTD.

TEL:886-2-8919-1288 FAX:886-2-8919-1298 WEB:www.coremaster.com.tw

LCB3216-601Y-N

