

Aluminum Electrolytic Capacitor Specification				
Series	KLF	50 V 4.7 μ F	Part No.	KLF-050V4R7MC110-T2.5
Customer No.	/		Case size	Φ D 5 X L11
Specification	Items		Standard	
	Operating temperature range		- 40 ~ + 105 °C	
	Capacitance tolerance		\pm 20% (20°C , 120Hz)	
	Dissipation factor (MAX)		(Less than) 0.12(20°C , 120Hz)	
	Leakage current (MAX)		(Less than) 3 μ A (20°C 50 V 1 min)	
	Impedance (MAX)		/	
	Ripple current (MAX)		60mArms (100kHz , 105°C)	
	Load life		5000hrs	
Outline	Sleeving pipe basic		PVC	
	(Dimensions)			
	<p style="text-align: center;">Copper clad steel wire(tinned)</p> <p style="text-align: center;">Sleeve</p> <p style="text-align: center;">Markings</p> <p style="text-align: center;">Φ0.5\pm0.05</p> <p style="text-align: center;">Flat Rubber</p> <p style="text-align: center;">Lead space 2.0\pm0.5</p> <p style="text-align: center;">【Remarks:Taping space: 2.5 (+0.8-0.2)】</p> <p style="text-align: center;">(unit):mm</p>			
Recorder	(The first edition) : 2017-7-1			
Wrote by: LUOLI		Checked by: DINGCHANGHUA		Approved by: SHENZHIHONG