



Representative Image

Ref. No. 606164 | Cat. No. BPA440/030

Description: RCCB Residual current circuit breaker BP A 4P 40 A 30 mA

EAN 5413656061649

Products > Modular DIN-rail devices > People protection > People protection

Series BP/BD - Residual Current Circuit Breakers
People protection against the risk of electrocution.
Features and benefits

- In accordance with IEC 61008
- Additional protection for people (up to 10/30mA) and property (above 30mA)
- Ratings 16A,25A,40A,63A,80A and 100A
- 30mA,100mA,300mA, 500mA and 1000mA sensitivity options
- 2P 2Module, 4P 4Module
- High resistance to nuisance tripping
- Type AC, A, S, B, or types Ai and Si
- Can be fitted with auxiliary contacts

Descriptors

Category	People protection
----------	-------------------

Specifications

Series	Residual current circuit breaker
Range	BP
Type	Type A
Serie	Series A
Un	240/415 Vac
Poles	4P
Rated current In	40 A
Residual current	30 mA
Operating time	Instantaneous
AC/DC	AC
Number of modules	4
Terminal capacity flexible/rigid cable	35-50 mm ²
Tropicalisation according to IEC 60068-2-28/2-30	95%RV at 55°C
Electrical service life	20000/10000
Selectivity class	3
Minimum servicevoltage	205 V
Frequency	50/60 Hz
Operating temperature	-25°C / +40°C
Storage temperature	-25°C / +70°C
Shock voltage	6
Protection Degree	IP20
Ambient temperature	-25°C / +40°C
Nominal current Un	240-415 Vac
Nuisance tripping resistance	250 A 8/20 μs
Nominal current	Im = 500 A
Differential making and breaking capacity	I(Δ)m >= 500 In
Short circuit capacity	I _{nc} = 10000A at 240V/415V
Short circuit capacity / norm	fuse 80A gG

Specifications

Series	Residual current circuit breaker
Range	BP
Type	Type A
Serie	Series A
Un	240/415 Vac
Poles	4P
Rated current In	40 A
Residual current	30 mA
Operating time	Instantaneous
AC/DC	AC
Number of modules	4
Terminal capacity flexible/rigid cable	35-50 mm ²
Tropicalisation according to IEC 60068-2-28/2-30	95%RV at 55°C
Electrical service life	20000/10000
Selectivity class	3
Minimum servicevoltage	205 V
Frequency	50/60 Hz
Operating temperature	-25°C / +40°C
Storage temperature	-25°C / +70°C
Shock voltage	6
Protection Degree	IP20
Ambient temperature	-25°C / +40°C
Nominal current Un	240-415 Vac
Nuisance tripping resistance	250 A 8/20 µs
Nominal current	Im = 500 A
Differential making and breaking capacity	I(Δ)m ≥ 500 In
Short circuit capacity	I _{nc} = 10000A at 240V/415V
Short circuit capacity / norm	fuse 80A gG

Classifications

Approvals	CE, KEMA
Approval/norm	EN 61008
ETIM 5.0	EC000003
ETIM 6.0	EC000003

Dimensions

Weight	0.385 kg
--------	----------

Package information

Standard packing	1/3
------------------	-----

Publications

Title	Publication No.	Publication Type
RCCB Residual current circuit breaker - 4P 4modules - Series BP-BD (pdf)		
3D PDF Viewer: Modular DIN-rail device - People protection - RCCB Residual current circuit breaker - 4P 4modules - Series BP-BD (3DPDF format)	3D-01108-PDF	Drawings - CAD - 3D
RCCB Residual current circuit breaker - 4P 4modules - Series BP-BD (stp)		
3D Drawing: Modular DIN-rail device - People protection - RCCB Residual current circuit breaker - 4P 4modules - Series BP-BD (STEP format)	3D-01108	Drawings - CAD - 3D

Additional Documentation: Visit our [Publication Library](#) to find technical documentation, specifications, catalogues, promotional literature, 3D's,...